

Balcony Blinds

Range of External Blinds

Multi-Stop Channel (Twist Lock)

This manually operated blind is with Spring operation only. The Twist Base Bar is used to operate the blind by releasing the blind and moving it up or down, then it is locked back into place within the side channel. This operation is therefore more suited to small to medium sized blinds.

Available in a range of fabrics Sunscreen and Acrylic Canvas.



Café

Manually cord operated, rolls up from the bottom. Comes with zips and has optional Valance to assist with further weather control.

Available in a range of fabrics from a Clear PVC to a transparent or translucent Sunscreen.



Spring Rollup

Manually operated Spring Rollup blinds are only available as Spring operated. This blind is suited to a small sized blind. The operation of this blind requires it to be fastened to the ground or balustrading.

Available in a range of fabrics from Sunscreen options to Acrylic Canvas.



Wire Guide Straight Drop

These blinds are suitable to be operated with crank operation or can be motorised. They are well suited to a medium to large sized area to a maximum width of 5800mm. The Wire Guides run from the bracket area of the blind, down at a slight distance from the fabric and are then fitted to the bottom rail. This contains the wire guides to prevent blowing around in the wind.

Available in a range of fabrics from a Clear PVC, Sunscreen options and Acrylic Canvas.



Balcony Blinds

Range of External Blinds

Heavy Duty Channel

These blinds are suitable to be operated with crank operation or they can be motorised. Perfect for a medium to large sized area, to a maximum width of 6000mm. The Bottom Rail travels inside the channel that is fitted at the top near the Bracket area of the blind and down the full drop of the blind. This assists in containing the blind fabric to prevent blowing around in the wind.

Available in a range of fabrics from a Clear PVC, Sunscreen options and Acrylic Canvas.



Straight Drop Crank Operated

This manually operated blind (not suitable for motorisation) is well suited to blinds of medium to larger size to a maximum width of 5800mm. As this blind is used externally and does not have side channels or wire guides, it must be anchored, or it will blow around in the wind.

Available in a range of fabrics from a Clear PVC, Sunscreen options and Acrylic Canvas.



Cord-n-Pulley

Manually cord operated, rolls up from the bottom. Does not have zips on the side.

Available in a range of fabrics from a Clear PVC, Sunscreen options and Acrylic Canvas.



Warranty

- All have 1 year Installation Warranty
- Fabrics recommended from HVG and Ricky Richards are 10 years and Clear PVC 5 years



AMBIENCE

BLINDS • SHUTTERS • AWNINGS

www.ambienceblinds.com.au